

	ST QUARTER (E1/2 NW1/4), ALL IN SECTION 12, TO	D WNSHIP 1 SOUTH, RANGE 14 WEST, SALINE COUNTY,	E
OUNTY, ARKANSA O A FOUND 1/2" F (SIDE ADDITION, ST ALONG THE W SAID WEST LINE A O A SET 1/2" REB GHT OF WAY, 75. OF 164.75 FEET (1573; THENCE SO OF 37.63 FEET TC SOUTH 6°12'28" W O A POINT; THENO	AS AND RUN THENCE NORTH 1°46'27" EAST ALONG REBAR WITH CAP #1573 FOR THE POINT OF BEGI PHASE 1, A DISTANCE OF 342.89 FEET TO A FOUN VEST LINE OF SAID E1/2 NW1/4 A DISTANCE OF 829 A DISTANCE OF 487.60 FEET TO A SET 1/2" REBAR BAR WITH CAP #1573 ON THE EAST RIGHT OF WAY .00 FEET TO A SET 1/2" REBAR WITH CAP #1573; THENCE S OUTH 87°55'11" EAST A DISTANCE OF 75.00 FEET O A POINT; THENCE SOUTH 38°51'03" WEST 22.04 F VEST 37.28 FEET TO A POINT; THENCE SOUTH 21°2 CE SOUTH 34°41'56" WEST 114.30 FEET TO A POINT 1 FEET TO THE POINT OF BEGINNING , CONTAINING	T; THENCE SOUTH 2°01'49" WEST FOR 761.91 FEET TO A IG 10.78 ACRES MORE OR LESS. 205-00074-000 CARLOS & LARA ARREOLA 2904 MIDLAND ROAD FND 1" HEX ROD	25 0 50 25 0 50 M (R (P RVEY PLAT CODE: -14W-0-12-400-62-1573 D/
·	22 24976 SQ.FT		$\begin{array}{c ccccccccccccccccccccccccccccccccccc$
FT. ES		<u>− - S2° 04' 49"W - 324.82' − − − − − − − − − − − − − − − − − − −</u>	$\begin{array}{c ccccccccccccccccccccccccccccccccccc$
	46.041 S33°56 28 W Sq. 66 33 SF 28 W	20 15566 SQ.FT	
	340.19'		
			[] 0.3 [] 0.3 [-] 14560 SQ.FT [-] [-] [-] [-] [-] [-] [-] [-] [-] [-] [-] [-] [-] [-] [-] [-] [-] [-] [-] [-] [-] [-] [-] [-]
X-	10' EXCLUSIVE SEWER EST	-0	
	CREEKSIDE ADI	DITION, PHASE 2	STATE OF ARKANSAS EGISTERED FESSIONAL
	Curve Table		NGINEER NO. 9551
	Curve # Length Radius Chord Direction Chord L C11 81.79 75.00 N29° 12' 46"W 77.80 C12 35.95 75.00 N74° 11' 16"W 35.61 C13 39.27 25.00 N42° 55' 11"W 35.36 C14 39.27 25.00 S47° 04' 49"W 35.36 C16 12.25 25.00 S11° 57' 22"E 12.13	OCUMENTS USED: SURVEY PLAT OF RECORD RASBURRY SURVEYING 10/23/2014 DEED OF RECORD 2014 PAGE 25641 WILLIAMS TO DIAMOND DEVELO DEED OF RECORD 2004 PAGE 112595 THOMAS TO DIAMOND DEVELO SURVEY PLAT OF RECORD MIDLAND FARM SUBDIVISION BY HENRY N	PMENT II
ey made by	C17 48.18 60.00 S2° 59' 15"E 46.90		
rey made by he ich were	C17 48.18 60.00 S2° 59' 15"E 46.90 C18 48.61 60.00 S43° 13' 31"W 47.29 C19 61.35 60.00 N84° 16' 23"W 58.71 C20 123.28 60.00 N3° 52' 51"E 102.71 C21 23.55 25.00 S60° 56' 08"E 22.69 C22 62.02 60.00 N65° 03' 27"E 347.10 C23 45.59 60.00 N20° 48' 40"E 45.88	BASIS OF BEARINGS: BENCHMARK(S) PROVIDED ARE REBAR AND COORDINATES ON BENCHMARKS DATUM 1983, ARKANSAS SOUTH ZONE, US SURVEY FEET, GRID COORDINATE NAVD 1988. COORDINATES AND ELEVATIONS WERE ESTABLISHED USING GPS USING THE NATIONAL GEODETIC SURVEY'S "ONLINE POSITIONING USEF CERTIFICATIONS:	S AND ELEVATIONS ARE AND WERE PROCESSED
ne	C18 48.61 60.00 S43° 13' 31"W 47.29 C19 61.35 60.00 N84° 16' 23"W 58.71 C20 123.28 60.00 N3° 52' 51"E 102.71 C21 23.55 25.00 S60° 56' 08"E 22.69 C22 62.02 60.00 N65° 03' 27"E 344.88	BENCHMARK(S) PROVIDED ARE REBAR AND COORDINATES ON BENCHMARKS DATUM 1983, ARKANSAS SOUTH ZONE, US SURVEY FEET, GRID COORDINATE NAVD 1988. COORDINATES AND ELEVATIONS WERE ESTABLISHED USING GPS USING THE NATIONAL GEODETIC SURVEY'S "ONLINE POSITIONING USER	S AND ELEVATIONS ARE AND WERE PROCESSED SERVICE" (OPUS).

